

**1. 2011 John Deere Gator 625i utility side-by-side UTV
VIN 1M0625GSCBM013557**

Engine

617cc, V-twin-cylinder, water-cooled, four-cycle, OHV, gasoline engine, electronic fuel injection, 23hp, 32.9 lb-ft torque at 2100 rpm, electric start. Overhauled May 2022

Transmission

Continuously variable belt drive transmission (CVT), 4x4 wheel drive, primary front wheel drive shaft, reverse/neutral/forward, Hi/Lo drive modes, lock/unlock rear differential.

Cargo Bed

45"L x 53"W x 12"H, 16.4 cu ft steel cargo body, 1000 pound load capacity, electro/hydraulic bed lift

Wheels & Tires

27 inch alloy wheels, all terrain 27 x 9.00-R14 front tires, 27 x 11:00-R14 rear tires, one front and one rear spare tire trailer mounted

Brakes

Front and rear hydraulic disc brakes with engine breaking

Suspension

Front independent double A-arm suspension with stabilizer bar, 8 inch travel, Rear independent double A-arm suspension with stabilizer bar, 9 inch travel, two shock absorbers, rack & pinion steering, ground clearance 11 inches

Dimensions

116 inches length, 62 inches wide, 75 inches high, 79 inch wheelbase, 12.4 foot turning radius

1450 pounds dry weight, 1400 payload capacity, 1500 pound tow capacity, 7 gallon fuel capacity

Interior

Two side by side vinyl folding bucket seats, hour meter, fuel gauge, over temp warning light, two 12 volt power outlets, two cup holders,

Exterior

Front and rear bumper, light guard, front side protectors, rear side protectors, front mud guards, rear mud guards, CV boot covers, drive shaft skid protector,

ROPS roll cage, cab/bed divider, hood cargo rack, Warn 3000 pound front winch with fairlead

Lights

Halogen headlights, body mounted LED warning lights, front, side and rear LED scene lights

2. 2014 Holmes utility trailer, VIN 5LVBL1421FA3027

82 inch wide x 14 feet long, one 3.5k electric brake axle, one 3.5K idler axle, GVWR 7,000 lb, four ST205/75/D15 tires, one spare trailer tire, 15x5.5 J rims, 2 5/16 inch coupler, fully sealed wiring harness, black powder coated frame, dual 4 foot rear gate with spring latches, EZ lube axles, diamond tread steel fenders, 2k jack with sand foot, treated No. 2 yellow pine floors, D ring floor mounts (4), high mount tail lights, rail sides, all LED lighting, 3x2x1/4 angle frame, 4 inch channel tongue, 3x2x3/16 cross members, tongue mounted aluminum diamond tread storage box

3. Kimtek Fire/EMS Skid

Firelite Transport Deluxe FDH-203, 48" W x 55" L x 38" H, all aluminum diamond tread construction, 55 gallon poly water tank, rescue stretcher/backboard area with two 48" stainless steel grab rails, storage area, below rescue area, Hannay F4024-17-18 manual rewind hose reel, Darley-Davy pump 65 GPM @ 48 PSI; 50 GPM @ 81 PSI; 20 GPM @ 120 PSI, Honda GX160 4.8 net hp at 3600 RPM, 3.9 hp continuous at 3600 RPM

Package price \$19,995. Will not part out the package.